Development Data Boot Camp Intro to Stata: More tricks in exploring data

Ge Sun

University of Notre Dame

May 17, 2023

Outline

Econometrics variable types: dummies, categorical, and continuous

Other useful commands in exploring data

Outline

Econometrics variable types: dummies, categorical, and continuous

Other useful commands in exploring data

- ► A Dummy variable usually appears in the regression analysis to represent subgroups of the sample.
- ▶ It can only take two values: 0 and 1

- ▶ A Dummy variable usually appears in the regression analysis to represent subgroups of the sample.
- ▶ It can only take two values: 0 and 1
- ▶ How would this two-dimensional dummy variable can represent the subgroup?

test scores	girls	boys
89	1	0
73	1	0
56	0	1
92	1	0
87	0	1
64	1	0

^{*} How many girls are in this sample?

- ▶ A Dummy variable usually appears in the regression analysis to represent subgroups of the sample.
- ▶ It can only take two values: 0 and 1
- ▶ How would this two-dimensional dummy variable can represent the subgroup?

test scores	girls	boys
89	1	0
73	1	0
56	0	1
92	1	0
87	0	1
64	1	0

- * How many girls are in this sample?
- * About debugging: Make sure that dummies variables successfully regulate exclusive subgroups.

- ► A Dummy variable usually appears in the regression analysis to represent subgroups of the sample.
- lt can only take two values: 0 and 1
- ▶ How would this two-dimensional dummy variable can represent the subgroup?

test scores	girls	boys
89	1	0
73	1	0
56	0	1
92	1	0
87	0	1
64	1	0

- * How many girls are in this sample?
- * About debugging: Make sure that dummies variables successfully regulate exclusive subgroups.
- * What does mean(girls) mean?



- ▶ A Dummy variable usually appears in the regression analysis to represent subgroups of the sample.
- ▶ It can only take two values: 0 and 1
- ▶ How would this two-dimensional dummy variable can represent the subgroup?

test scores	girls	boys
89	1	0
73	1	0
56	0	1
92	1	0
87	0	1
64	1	0

- * How many girls are in this sample?
- * About debugging: Make sure that dummies variables successfully regulate exclusive subgroups.
- * What does mean(girls) mean?
- * What would I get if



Categorical variables

- ▶ Variables that take a list of (integer) numbers to indicate each observation belonging to a particular group.
- **Example:**

educational level	illiterate	primary school	secondary school
edu	1	2	3

► Can I add or subtract categorical variables?

Categorical variables

- ▶ Variables that take a list of (integer) numbers to indicate each observation belonging to a particular group.
- Example:

educational level	illiterate	primary school	secondary school
edu	1	2	3

- Can I add or subtract categorical variables?
- Categorical variables are like the ordinal number (compared with cardinal number). You can compare them but you can not calculate them. It is like that you can not say that people finishing secondary school are twice as smart as people finishing primary school.

The new dataset with more continuous variables

- Quarterly Labour Force Survey (QLFS) in 2008, fourth quarter.
 - * Abstract It is a household-based sample survey conducted by Statistics South Africa (Stats SA). It collects data on the labour market activities of individuals aged 15 years or older who live in South Africa.
 - * Kind of data: Sample survey data
 - * Unit of analysis Individual
- ▶ Question: Can you give some examples of categorical variables in the dataset? Are there any dummy variables?

The data source link

Outline

Econometrics variable types: dummies, categorical, and continuous

Other useful commands in exploring data

Let's generate all group dummies at once!

► A magic way to generate dummy variables:

tab categorical_var, gen(dummy)

Let's generate all group dummies at once!

A magic way to generate dummy variables:

```
tab categorical_var, gen(dummy)
```

- ► Regular expressions "*"
 - * regular expressions use a notation system that allows for matching complex patterns of text with minimal effort
 - * "*" means: match zero or more

Example

```
tab Sector_Sep2003, gen(work_type) des work_type*
```



Manipulating categorical variables

- ▶ Command *recode* helps you recode *categorical* variables.
 - * Example:

which is equivalent to

$$\begin{array}{c} \text{gen race_new} = \text{race} \\ \text{replace race} = 2 \text{ if race_new} == 4 \end{array}$$

Command: recode

- ▶ It is useful when you have a bunch of survey questions, like our CIF, where you use 1-5 to express "Strongly disagree" to "Strongly agree". But the numbers in different questions have different meanings.
- It is also useful to handle missing values.
 - * the survey has missing values for many reasons:
 - refuse to answer this question
 - did not take the survey
 - the answer they give does not make sense

 $codebook \ Sector_Sep 2003$

codebook Sector_Sep2003

- Let's make a value label for our new race_new variable
- ▶ We will make the label called "black" when race_new is 1 and called "white" when the race_new is 2.

codebook Sector_Sep2003

- Let's make a value label for our new race_new variable
- ▶ We will make the label called "black" when race_new is 1 and called "white" when the race_new is 2.
- This is a two-step process:
 - 1. We first define the label:

label define race_newl 1 "black" 2 "white"

2. Then we assign the label to the variable:

label values race_new race_newl

codebook Sector_Sep2003

- Let's make a value label for our new race_new variable
- ▶ We will make the label called "black" when race_new is 1 and called "white" when the race_new is 2.
- ► This is a two-step process:
 - 1. We first define the label:

label define race newl 1 "black" 2 "white"

2. Then we assign the label to the variable:

label values race_new race_newl

If you want to rename the label value, you need to first drop the old one:

label drop race_newl



codebook Sector_Sep2003

- Let's make a value label for our new race_new variable
- ▶ We will make the label called "black" when race_new is 1 and called "white" when the race_new is 2.
- This is a two-step process:
 - 1. We first define the label:

label define race_newl 1 "black" 2 "white"

2. Then we assign the label to the variable:

label values race_new race_newl

If you want to rename the label value, you need to first drop the old one:

label drop race_newl

Another trick:

label list



Command: list and sort

list: list values of the variables

 $\begin{array}{c} \text{list in } 1/5 \\ \text{list in -5/L} \\ \text{list edyears earnings_week in } 1/10 \\ \text{list edyears earnings_week in } 1/10, \, \text{sep(4)} \end{array}$

sort: arrange observations into ascending order

sort earnings_week sort earnings_week edyears

* Question: What if you want to arrange observations into descending order?



Command: egen

- ► The *egen* command is an extension to *gen* that enables creation of variables that would be difficult to create using *gen*
- ► For example, suppose we want to create a variable that for each observation equals sample average earnings.

```
egen ave_earnings = mean (earnings)
```

- by: We can use the by function to create variables within groups, but in order to use by you must sort beforehand. Thus, we recommend to use bysort instead.
- bysort + egen: the powerful and important code we have when cleaning and managing dataset
 - * bysort Indus_Sep2003: egen industry_mean = mean(earnings_week)

- by: We can use the by function to create variables within groups, but in order to use by you must sort beforehand. Thus, we recommend to use bysort instead.
- bysort + egen: the powerful and important code we have when cleaning and managing dataset
 - * bysort Indus_Sep2003: egen industry_mean = mean(earnings_week)
 - * bys Prov_Sep2003: egen sum_employers = sum(Q44NrEmp_Sep2003)

- by: We can use the by function to create variables within groups, but in order to use by you must sort beforehand. Thus, we recommend to use bysort instead.
- bysort + egen: the powerful and important code we have when cleaning and managing dataset
 - * bysort Indus_Sep2003: egen industry_mean = mean(earnings_week)
 - * bys Prov_Sep2003: egen sum_employers = $sum(Q44NrEmp_Sep2003)$
 - * bys Age_Sep2003: egen $count_age = count(UqNr)$

- by: We can use the by function to create variables within groups, but in order to use by you must sort beforehand. Thus, we recommend to use bysort instead.
- bysort + egen: the powerful and important code we have when cleaning and managing dataset
 - * bysort Indus_Sep2003: egen industry_mean = mean(earnings_week)
 - * bys Prov_Sep2003: egen sum_employers = sum(Q44NrEmp_Sep2003)
 - * bys Age_Sep2003: egen $count_age = count(UqNr)$
 - * bys Prov_Sep2003: egen x = sum(female)